

## VD8A SECTIONAL VALVE

<b>MODEL</b>	VD8A
<b>TYPE</b>	SECTIONAL
<b>FLOW</b>	90 LPM
<b>CIRCUIT</b>	PARRALLEL & SERIES
<b>MAX PRESSURES</b>	P=350bar A&B=350bar T=25bar
<b>MAIN RELIEF</b>	Std 175 bar, Options Available
<b>PORT RELIEF</b>	OPTIONAL
<b>POWER BEYOND</b>	OPTIONAL
<b>PORTS – UNO(BSP)</b>	P=7/8(3/4) A/B=7/8(1/2) T=1-1/16(3/4)



<b>NUMBER OF SPOOLS</b>	1 TO 8
<b>SPOOL TYPES</b>	CYLINDER MOTOR SINGLE ACTING FLOAT
<b>SPOOL CONTROLS AND OTHER OPTIONS</b>	MANUAL PNEUMATIC CABLE REMOTE 12V SOLENOID 24V SOLENOID MICROSWITCH JOYSTICK (2 SPOOL) DETENT HYDRAULIC PILOT PRIORITY INLET 12 & 24V INLET DUMP VALVE 12 & 24V PORT DUMP VALVE COMBINE WITH VD6A MID INLET – SPLIT OR COMBINED ELECTRO-PROPORTIONAL

